



AUREOLE ELECTRICALS & ELECTRONICS PVT LTD



TECHNICAL SPECIFICATION : 200W HIBAY CW

OPERATING VOLTAGE	100-300V
INPUT VOLTAGE	230V \pm 10 %
INPUT CURRENT(ma)	881 ma
POWER(W)	200
POWER FACTOR	0.98
THD(%)	<10%
DRIVER EFFICIENCY(%)	>85
LINE REGULATION	90-330V
AUTO CUTT OFF PROTECTION	300-315V
RECOVERY VOLTAGE	290-295V
LED	LM 80 CERTIFIED LED
LED MAKE	MLS/BRIDGELUX/EVERSTAR
LED TYPE	2835/1W/9V /100 MA
NO OF LED	240
LED CHIP EFFICACY	135-145LM
LUMEN/W (\pm 10%)	110
LUMEN (\pm 10%)	27500 LM
CCT (6000K \pm 500K)	5500-6500 K
CRI (>70)	70-75
LED BEAM ANGLE	120
LUMEN MAINTENANCE	50,000 HRS @ L70 FOR LED
OPERATING TEMPERATURE RANGE	-10+50 degree
HUMIDITY RANGE	10% TO 95% RH
INGRESS PROTECTION	IP 66
WARRANTY PERIOD	2 YEARS
MAIN HOUSING	Excellent thermally managed Pressure die cast aluminium
FRONT COVER	NA
LENS	POLYCARBONATE LENS.
HARDWARE	SS OR MS Zinc Plated & Passivated

PROTECTIONS : OPEN & Short circuit protection, over voltage , over temp , surge protection(>5KV), H.V (1.5KV), IR (>100 M n)

AS PER APPLICABLE INDIAN STANDARD

APPLICATIONS : WARE HOUSE , INDUSTRIAL SHEDS, SUPER MARKETS, MANUFACTURING UNITS

PREPARED BY - AKRAM SIDDIQUE.

AUREOLE ELECTRICALS : B-83/5/2 , MUNDKA INDUSTRIAL AREA - 110041,
NEW DELHI